

# LED Street light

SKU:SRSL030W-230V

## Information

- Excellent Street Lighting for safer, clearer and more uniform road environment.
- This product waterproof and dustproof level 65. Can be used in various of places
- Green lighting source is not only reliable and durable, but also low maintenance cost.
- Adopted 2835/3030 SMD Led light source, Large-Size Chip with High brightness and low light fades,
- Enough Current margin, Led chip Rated current 150mA, actual use only 120mA.
- Extend led Lights lifespan and increase Light Efficiency.
- Integrated fixture structure, Air convection design for reliable lifetime.



## Application



Streets



Urban areas



Roads



Motorways




Parking areas



Pedestrians crossings

- ◆ Light controller (optional)
- ◆ Lightning protection
- ◆ Lumileds/ Philips Leds/ Sanan Leds
- ◆ ZHIHE LED Driver
- ◆ System efficacy is up to 130~150LM/W
- ◆ Surge protection-SPD level of 10KV

### Lightning arrester



### LED Driver



### Light Controller Style




### Common Style



## Installatio


### ① Wiring, as shown in Figure 1.

AC input: L (brown or red)- firewire, N (blue or black)- neutral,(yellow-green)-ground line;



### ② Install the pole, as shown in Figure 2.

Put the pole into the lamp arm and fix the screw with a hex wrench. Be careful not to lock it;



## if with light controller


### ③ Adjust the angle as shown in Figure 3.

3. Adjust the lamp body horizontally to make the lamp body and the ground Vertically, tighten the screws with a hex wrench;




### ④ Install the Photocontrol, as shown in Figure 4.


Place the photocontrol on the lamp body and lock it;



### ⑤ Assembly is completed, as shown in Figure 5.



## Dimensions (mm)



- L : 260mm
- W: 150mm
- H : 65mm
- Installation Pole: 40mm

Adapter: 40mm - 60mm



# LED Street light

SKU:SRSLO30W-230V



## Specification

Product	SRSL030W-230V		
Norminal Wattage	30W		
LED Qty	40 PCS		
Input Voltage	AC220-240V 50/60Hz		
Luminaires Class	Class I		
LED Brand	Lumileds/ Philips Leds/ Sanan Leds 2835SMD/3030SMD		
Driver Brand	ZHIHE		
Operating Temperature	-20℃to+50℃		
Power Factor(PF)	≥0.95		
THD	<20%		
CCT	3000K (Warm White)	4000K (Nature White)	6000K (Cool White)
Lumen Output (+/- 5%)	3900lm±10%	4500lm±10%	4500lm±10%
Luminaire efficacy (+/- 5%)	130LM/W±10%	150LM/W±10%	150LM/W±10%
Beam Angle	135° x70°		
CRI	≥70Ra		
Rating	IP65		
Material	Die-cast aluminum + optical glass		
Suit for Light pole	Φ40		
Shell Color	Gray other RAL colors available on request		
Accessories (Optional)	Common	Light controller	
Product Size(mm)	L260xW150xH65	L260xW150xH135	
Packaging Type	1*10layer=10PCS/carton	1*10layer=10PCS/carton	
Packaging size(mm)	L395xW365xH390	L745xW365xH390	
N.W.	13.9KG	16.8KG	
G.W.	15.8KG/ Carton	18.7KG/ Carton	
Lumen Maintenance	> 50,000 hours-L <sub>70</sub> at 25 °C		
Certifications	CE、RoHS		

# LED Street light

SKU:SRSLO30W-230V

## Test Report



## Install suggestion

