

18W LED PANEL LIGHT

HIGH POWERED

300x300mm| IP41

SKU:SRPL300X300-18W

INFORMATION

Measuring 300mm x 300mm, this IP41 rated 18W panel light typically replaces 600mm T8/T5 fluorescent tubes lights set in 600x600 grids. Which is why they're the popular lighting choice for hotels, factories, offices, schools, colleges, hospitals and the like. Energy use will be reduced by up to 50% and you'll notice a dramatic improvement in light quality.

While fluorescent tubes tend to flicker towards the end of their life, panel lights maintain their brightness and quality for a much longer period and these 18w units could use a flicker free LED driver for improved uniformed light distribution with no interference.

They also last far longer. This 36W panel will give you 49,999 hours of service, which is up to 20 times longer than your older light source.



FEATURES

- ◆ Colour Option (CCT): 3000K, 4000K, 6000K
 - ◆ Lumens: 1530 + / - 5%
 - ◆ Beam angle: 120 Degree
 - ◆ Life span: 49,999Hrs
 - ◆ IP Rating: IP41
 - ◆ CE & RoHS Certified
- ◆ 5 years warranty



TECHNICAL PARAMETER

- ◆ Input: AC 200-240V 50/60Hz 420ma
- ◆ Output Current: DC 27-42V
- ◆ LED Type: 4014 SMD LED
- ◆ Output Power: 18W
- ◆ Light Guide Plate (LGP): PMMA

Tsong is constantly developing and improving its products. For this reason, all product descriptions are intended as a general guide and we may change specifications time to time in the interest of product development, without prior notification or public announcement. Data in this sheet has been obtained in controlled experimental conditions. However, Tsong cannot accept any liability arising from the reliance on such data to the extent permitted by law.

APPLICATIONS

- ◆ Hotels
- ◆ Conference/Meeting rooms
- ◆ Factories and offices
- ◆ Schools, colleges, universities and hospitals



18W LED PANEL LIGHT

HIGH POWERED

300x300 mm | IP41 Rating



SKU: SRPL300X300-18W

SPECIFICATIONS




Model#	CCT	Lumen (lm)	CRI	Beam angle	Voltage	PF	Weight (kg)
SRPL300X300-18W	3000K	1440	>80	120°	AC200-240V	≥0.95	1.2kg
SRPL300X300-18W	4000K	1530	>80	120°	AC200-240V	≥0.95	1.2kg
SRPL300X300-18W	6000K	1530	>80	120°	AC200-240V	≥0.95	1.2kg

PRODUCT PACKAGING INFORMATION

1. 10 pcs per carton
2. Gross Weight: 16.5 kg
3. Packing Size (LxWxH): 365x295x400

All dimension units are in mm

Dimension(Unit:mm)



INSTALLATION AND ACCESSORIES

- ◆ Hanging Kit for suspended installation
- ◆ Mounting frames installation
- ◆ TRAIC/0-10v Dimmable driver options

